



LEAN DRUM

- Wash and Blow-off in One Small Package
- Engineered for Lean/Cellular Manufacturing
- Energy Efficient Design
- Single Point Utility Connection
- Easy Maintenance Design

Lean Drum - Series LD-15 / LD-18

All specifications are subject to change without notice



CLEANING TECHNOLOGIES GROUP

RANSOHOFF • BLACKSTONE-NEY ULTRASONICS • CTG ASIA

MODEL NUMBER	LD-15	LD-18
PART PRODUCTION	4 CU FT/Hour @ 2PRM design drum speed	12 CU FT/Hour @ 2PRM design drum speed
WASH CAPACITY	75 Gallons (280 Liters)	200 Gallons (760 Liters)
RINSE CAPACITY	75 Gallons (280 Liters)	200 Gallons (760 Liters)
BLOWER CAPACITY	550 CFM @ 6" SP	875 CFM @ 6" SP
DRUM DIAMETER	15" (380mm)	18" (460mm)
LOAD HEIGHT	48" (1220mm)	48 3/4" (1240mm)
UNLOAD HEIGHT	28" (710mm)	20 3/4" (530mm)
FLOOR SPACE (LXWXH)	8'1" X 4' X 4' 9" (2438 mm X 1220mm X 1448mm)	8'7" X 6'8" X 6'7" (2616mm X 2032mm X 2007mm)
UTILITY REQUIREMENTS	460V 3 Ph, 60 Hz	460V 3 Ph, 60 Hz

Ransohoff
(800) 248-9274
4933 Provident Drive
Cincinnati, OH 45246
www.ctgclean.com

Blackstone-NEY Ultrasonics
(800) 766-6606
P.O. Box 220
9 N. Main St.
Jamestown, NY 14702-0220

CTG Asia
(86)0512-66161698
56 Songshan Road
Suzhou New District
Jiangsu Province, China PRC: 215151